TVIP-IntercomPA

Complete integrated vandal resistant intercom assembly attaches to the network. Includes vandal resistant intercom with push-button, Network Interface Unit and Talkmaster software for Windows PC.

Call-in Station

Vandal-resistant call-in station with integral speaker/microphone and momentary, normally open, push-to-call button. Shown with hooded, surface mount, outdoor enclosure. The faceplate is 12-gauge, brushed stainless steel.

Integrated network interface powered by PoE uses Talkmaster software to communicate to Windows computer(s).



Outdoor Intercom Shown with optional hood



IP7-Network Interface

- Half-duplex two-way audio
- Clear, crisp audio using 64 kbps bandwidth
- Utilize existing IP Network Infrastructure
- Operates over wired, wireless or fiber networks
- Power over Ethernet (PoE)
- On-board relay and sensor for door/gate access control and management
- Flexible Audio I/O supports Electret or Dynamic microphone and Line In/Out
- Electronics mounted behind intercom panel
- Connect to VoIP Systems via TalkMaster[™] SIP Media Gateway
- Optional outdoor housing

SPECIFICATIONS

Faceplate: 12 gauge brushed stainless steel Speaker: 2.5" 8 Ohm, waterproof cone. Freq Response 200-20k Hz

Sound Level: 90 dB at 1-Watt, 1 Meter

Microphone: Omnidirectional Electret, water resistant **Call Button:** Momentary (normally open) push-to-call with LED

Mounting Flush mount in 2-Gang box (min. 2" deep) or surface mount using optional PNL-BB6 or PNL-BB7 (Hooded) Box

NETWORK

Protocols: TCP, UDP, RTP, SIP, ICMP, IGMP Multicast Interface" 10/100 Base-T Ethernet, Auto-MDIX, RJ45 IP Address: Static, DHCP PoE Standard: 802.3af (6.5W)

Bandwidth: 64kbps (Voice)

Software and Connectivity

TalkMaster[™] Focus Endpoint

SIP 2.0 Endpoint Hybrid TalkMaster™ Focus/SIP 2.0 Endpoint

MODELS:

TVIP-intercomPA-O-2G: 1 watt, PoE, Flush mounted Intercom for 2-Gang installation with stainless steel front plate.

TVIP-intercomPA-O-BB: 1 watt, PoE, surface mounted intercom with metal back-box and hood



500 Executive Blvd. Ossining, NY 10562 800-431-1658, 914-944-3425, www.kintronics.com