

Pro-Series TVIP2R-Pro

IP Access Control Reader

RFID Proximity Access Control with Keypad and LCD display

Reader includes a touchscreen LCD display for management and pin code entry. Complete setup can be done using the touchscreen or computer running TVIP-TirSoft management software.



Features

- Multiple verification modes include credential and / or pin code
- Network attached with power over Ethernet (PoE) option
- Stores up to 50,000 credentials.
- USB flash interface for back up or transfer of database
- Easy management and operation. It can work by itself or with computer for large installations requiring centralized management
- Optional smartcard (MiFare) credential support
- Built-in camera stores 7,000 event snapshot history and 3,000 user photos
- Tamper sensor

Models

TVIP2R-Pro	RFID-proximity reader
TVIP2R-Pro-POE	Reader and PoE kit that includes high power injector and splitter
TVIP2R-ProMF	Adds the capability to use smart cards (MiFare)

Specifications

Touchscreen display	2.4-inch TFT-LCD
Network Attached	TCP/IP RJ45 connection
Power	12 VDC, 3A (adapter included) or PoE kit
Functions	Access Levels/Groups/Holidays, DST/Bell Schedule, Duress Mode (Password), Anti-Passback, Record Query, Custom Wallpaper & Screen Saver
Software for Windows Computer	Central software management—TVIPTirSoft
Dimensions	7.7 x 3.5 x 1.4 inches (195.5 x 87 x 35 mm)
Communication	TCP/IP, RS485 (for slave reader) USB Host Wiegand Input/Output
Lock and Door Interface	Lock Relay Output, Alarm Output/Auxiliary Input, Exit Button/Door Sensor, Doorbell Output
Credential capacity	50,000

KINTRONICS
IP Security Solutions

500 Executive Blvd. Ossining, NY 10562 800-431-1658, 914-944-3425, FAX 914-944-0717