TruView-Touch7

Video, Audio Multi-dialer IP Intercom Touch-panel Station

- Interactive 7-inch touch screen display allows users to select the apartment or person
- The Video Entry Unit controls door entry using a Smartphone App
- Administration portal provided by cloud web-browser interface
- Audio noise cancelation provides clear intercom sound
- Integrated IP Camera that can be viewed on App
- Fast to deploy, easy to maintain

The TruView-Touch offers more than the basic functionality of a modern door intercom. There are many excellent benefits: The visitor can easily select his contact person via name. If the selected person does not answer the call, alternative subscribers such as the colleague of the same group, a

Features

- Door Entry System is an exterior rated access call box for residential, multi-family and commercial applications.
- SIP/IP calling via POE

A single POE (power over ethernet) connection is used to provide both data and power to the TruView-Touch panel up to 300 feet from head-end.

• Video Calling to Phone, Tablet and PC

The resident will view who is at the door and be able to release the door-lock from the app giving access to the visitors. With one-way video, two-way voice, visitors will not be able to see the resident, but the resident will see the visitor.

• Video and Still Image - Date and Time Logging

The resident app and management portal display an image of all pin uses and a five second video of all video calls with date, time and name of resident called. Data is stored for 90 days and can be exported via csv.

• Group Calling

One call from the panel will call all devices in the group. Family groups can be added by management in the portal (resident control of this feature is due Q2-2020).

Limited Use Pins

This allows residents to send an entry pin from the MyDoorView app via text to a guest that will auto expire after pre-determined time and/or pre- determined number of uses from 1-99. All successful and failed pin uses will capture an image. More than five failed attempts in a row will notify management by SMS text and/or email with images.

Door and Gate Control

This helps management monitor the traffic and keep track of all vehicle's and/or people entering the property, creating entry logs.

• Anti-glare Tempered Touch Glass

Matte finish reduces glare, resists fingerprints, and supports gloved hands.

• Multi-purpose Mounts

Flush Mount, Surface Mount and Surface Mount with Rain Hood.





Specifications TruView-Touch7

Display	Panel Size	7" Diagonal
	Brightness	400nits
	Resolution	800 x 1280
Hardware	Processor	Quad Core A35
	RAM	2GB
	Storage	8GB
Operating System	OS	Android 8.1
Connectivity	Wifi	2GHz + 5GHz
	Ethernet	RJ45 10/100 (PoE)
	Digital I/O	Relay x 2 RS485
	USB	Micro USB x 1
Multimedia	Microphone	Echo cancelling mic
	Speaker	Waterproof Speaker, 2W x 1
	Camera	2M Camera with LED
Sensor	Sensor	G-Sensor for Tamper Alarm, Motion Sensor; Am- bient Sensor
Lighting	White	
Mounting	Mounts	Flush, Surface and Surface with Rain Hood
Power	Power Supply	Either 12V DC or POE
	Consumption	12W
Dimensions	10.25" x 5" x 1"	
Options	RFID Card Reader	Buzzer and LED, 125KHz/13.56MHz, EM4100, Mifare s50 S70, Desfire, FM1208





500 Executive Blvd. Ossining, NY 10562 800-431-1658, 914-944-3425, FAX 914-944-0717